

mediaJET® Litho White Matt | White matte inkjet paper

Product description

Litho White Matt is the perfect complement to “Litho Archival Matt”, slightly brighter in paper white with the same absolutely velvety soft surface, ideal as a cost-effective alternative to smooth artist papers. Excellent image carrier for valuable and archival photo posters, trade fair graphics, advertising posters, visualisations. Special inkjet layer enables premium, archival image output with very high colour space and excellent D-Max values.

Specific feature

mediaJET Litho White Matt is a completely new concept in inkjet paper with a light white colouration, which, thanks to its excellent price-to-performance ratio, represents a real alternative to the classic smooth artist paper and is suited to a wide circle of users. The special coating on the front for water-based printer systems, facilitates high ink acceptance characteristics with the best drying properties, a wide colour gamut and impressive, brilliant colours. Photographers will also appreciate this economically priced paper, which allows the printing of crisp images with resolutions of up to 5,760 dpi. We recommend mediaJET Litho White Matt for highend photoposters, portfolio folders and photo albums, exhibitions and trade fair graphics. In addition, it is the paper of choice for impressively rendered architectural drawings and technical visualisations. The paper is an approved quality and fulfils the requirements of DIN EN ISO9706.

Processing

To guarantee optimal quality, photo and fine art papers should be stored and processed in a climate with 30-70% relative humidity and at temperatures from 15-30°C. We recommend that the paper be acclimatised in the print room for one day before printing, and to reseal in the original package after printing. Prevent fingerprints on the coated side by wearing clean cotton gloves while processing. Please avoid contact with solvent, glue and softener, leads to yellowing.

Technical specification

Material:	Paper	Colour L:	97,2
Application Area:	only indoor	Colour a:	1,70
Surface:	Matt	Colour b:	-9,85
Specific gravity:	230,00g/m ²	UV Whiteness:	>140% (D65/10%)
Thickness:	265,00µm	PH Value:	7,5
B1-cert.:	no	Opacity:	>96%
Cold lamination:	yes	DIN ISO 9706 archive-resistant:	yes
Heat lamination:	yes	DIN ISO 16245:	no

This information consists of standard values for your guidance. Before using our print media, please check their suitability to your printer and for your intended application. Taking account of technical development, product specifications may be amended without prior notice at any time. There is no guarantee that the same results can be achieved. We not accept liability for any errors resulting from technical changes in printers and / or inks.